

TECHNICAL SHEET

TYPICAL APPLICATIONS



- Light weight carton sealing tape, suitable for manual dispenser application.
- Also for automated application.

ADVANTAGES AND BENEFITS

- Good adhesion even in recycled cartons.
- Long lasting adhesion

CONSTRUCTION

- Backing: Clear BOPP film.
- Adhesive: ECO SOLVENT
- Colour: Clear, white adhesive.



TECHNICAL DATA

| PP ECO SOLVENT | METRIC |
|-------------------------|-------------|
| Film Thickness | 25 Micron |
| Total Thickness | 45 Micron |
| Peel Adhesion | 2,8 N/cm |
| Tensile Strength | 35 N/cm |
| Elongation at break | 140% |
| Application Temperature | 5°C to 45°C |
| Service Temperature | 0°C to 50°C |



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

STORAGE

Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.