

TECHNICAL SHEET

TYPICAL APPLICATIONS

- Light weight carton sealing tape, suitable for manual dispenser application.
- Also for automated application.

ADVANTAGES AND BENEFITS

- Good adhesion even in recycled cartons.
- Long lasting adhesion

CONSTRUCTION

- Backing: Clear BOPP film.
- Adhesive: HOT-MELT (SYTHETIC RUBBER)
- Colour: Clear, white adhesive.



TECHNICAL DATA

PP HOT-MELT	METRIC
Film Thickness	25 Micron
Total Thickness	45 Micron
Peel Adhesion	4,8 N/cm
Tensile Strength	37 N/cm
Elongation at break	150%
Application Temperature	5°C to 45°C
Service Temperature	5°C to 50°C



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

STORAGE

Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.