

### TECHNICAL SHEET

#### TYPICAL APPLICATIONS

- Light weight carton sealing tape, suitable for manual dispenser application.
- Also for automated application.

#### ADVANTAGES AND BENEFITS

- Good adhesion even in recycled cartons.
- Excellent tack.
- Long lasting adhesion
- Ideal for storage in extreme temperature conditions and high moisture environments once applied.

#### CONSTRUCTION

- Backing: Clear BOPP film.
- Adhesive: Natural rubber and hydrocarbon resins.
- Colour: Clear, white or brown adhesive.



### TECHNICAL DATA

PP SOLVENT	METRIC
Film Thickness	25 Micron
Total Thickness	42 Micron
Peel Adhesion	2,1 N/cm
Tensile Strength	38 N/cm
Elongation at break	130%
Application Temperature	2°C to 45°C
Service Temperature	-25°C to 65°C



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

#### STORAGE

Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

#### SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.