

### TECHNICAL SHEET

#### TYPICAL APPLICATIONS

- Printable carton sealing PVC tape, suitable for manual dispenser application.



#### ADVANTAGES AND BENEFITS

- Good adhesion even in recycled cartons.
- Excellent tack.
- Long lasting adhesion.
- No noise, silent unwinding.
- Printable with vinyl inks.
- Easy unwind and fast printability.
- Once applied, ideal for storage in extreme temperature conditions and high moisture environments



#### CONSTRUCTION

- Backing: Unplastified clear PVC film.
- Adhesive: Natural rubber and hydrocarbon resins.
- Colour: Clear, white or brown adhesive.

#### TECHNICAL DATA

	METRIC
Film Thickness	32/33 Micron
Total Thickness	50/51 Micron
Peel Adhesion	2,4 N/cm
Tensile Strength	47 N/cm
Elongation at break	60%
Application Temperature	10°C to 45°C
Service Temperature	-25°C to 65°C



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

#### STORAGE

Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

#### SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.